


QuickE

 Electric Screwdriver **SLOKY**

0-TPK-ETS-16K-3.0
Handle

QuickE


Adapters

	Nm	0.6	0.9	1.2	1.4	2.0	3.0
In-lb		5.3	8.0	10.6	12.4	17.7	26.6

Bits

50mm		TX6	TX7	TX8	TX9	TX10	TX15
		6IP	7IP	8IP	9IP	10IP	15IP
		H1.5		H2.0		H2.5	H3.0


Art.-Nr.

7036271

SET-Preis, €

299,00
0-TPK-ETS-16K-5.0
Handle

QuickE


Adapters

	Nm	0.9	1.2	1.4	2.0	3.0	5.0
In-lb		8.0	10.6	12.4	17.7	26.6	44.3

Bits

50mm		TX7	TX8	TX9	TX10	TX15	TX20
		7IP	8IP	9IP	10IP	15IP	20IP
			H2.0		H2.5	H3.0	H4.0

Art.-Nr.

7036272

SET-Preis, €

299,00

QuickE Specification:

- For both manual and electric modes.
- Electric screw fastening with a protection function to prevent damage.
- 1/4" Hex drive.
- Built-in battery overcharging protection.
- LED light & Micro USB charging port.
- Rotation mode : Clockwise & Counterclockwise.

No Load RotationSpeed (max.)	300 r.p.m.
Ambient Temperature for charging	0-40°C
Max. Torque in Electric Mode	0.5 Nm
Max. Torque in Manual Mode	8.0 Nm
Length x Width x Height	150 x 40 x 40 mm

Drive Size	1/4" Hex (6.35 mm)
Charging Method	Micro USB 5V 1A
Battery Capacity	1.5 Ah
Battery Type	Lithium-ion
Battery Voltage	3.6V
Weight	186 g

 Scan for
user manual

Why Torque Control is important?

Increased tool life of fasteners. Deliver right tightening force to precise parts, no more over tightening. Enhance the function of both tightened parts and connected parts. Allows any user to deliver precision torque control, SOP is built. Apply for various applications.

Gültig bis 31.12.2026